
























	Standard	Result
 Size	EN ISO 24342	1500.0 mm x 250.0 mm
 Thickness	EN ISO 24346	4.5 mm
 Wear layer	EN ISO 24340	0.55 mm
Surface treatment		K-Guard+ PU coating
Guarantee¹	Light industrial	15 years
	Commercial	15 years
	Residential	Lifetime guarantee
 Bevelled edge		No
 Mass per unit area	EN ISO 23997	7470 g/m ²
 Standards	EN 649/EN ISO 10582	Pass
 Classification	EN 685/EN ISO 10874 - Light industrial	42: Light industrial general
	EN 685/EN ISO 10874 - Commercial	33: Commercial heavy
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy
 Reaction to fire	EN 13501-1	B _{fl} -s1
 Staining resistance	EN ISO 26987/EN 423	Excellent
 Light fastness	EN ISO 105-B02	Pass (≥ 7)
 Abrasion resistance	EN 649	Group T
	EN ISO 10582	Type 1
 Flexibility	EN ISO 24344	Pass
 Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0.10%)
 Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 13 dB
 Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0.1 mm)
 Castor chair continuous use	EN 425/ISO 4918	Pass
 Thermal resistance	ISO 8302	0.0245 m ² /K/W Suitable for underfloor heating. Max 27°C
 Slip resistance²	EN 13893	DS
	DIN 51130	R10
 Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
 Adhesive		Please install according to our installation instructions.
 Environmental	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions
	Environmental Product Declaration	External third-party verified Type III EPD
	NSF/ANSI 332	Sustainability Assessment for Resilient Floor Coverings; Silver certified product
	ISO 14001 / ISO 9001	Manufactured to quality and environment management systems standard
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms. Please see our website.



² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation alone the surface of the product can affect nominal values.

For more information:

UK: 01386 820104 | ROI: 01 6569887

Email: commercial@karndean.co.uk

Visit: www.karndean.com



21



20



Product Code	Size		Box Quantity		Slip Resistance	LRV
	mm	inches	m ²	Pieces	DIN 51130	
LLP301	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	20
LLP302	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	11
LLP303	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	11
LLP304	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	31
LLP305	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	20
LLP306	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	40
LLP307	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	21
LLP308	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	29
LLP310	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	31
LLP311	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	58
LLP315	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	14
LLP317	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	26

Wood Designs